## DISC HARROW

## Standard

- straight adjustable hitch
- road wheels: 340/55-16
- two rows of disc section Φ460 mm
- maintenance-free hub
- rubber protection for each plate
- hydraulic adjustment of the disc section operation
- rollers to choose: Cambridge, Zig-zag, Steel pack
- simplified unfolding system JACEK

vanish coating with improved parameters



hydraulically foldable, trailed



Options





## About the machine

The OX disc cultivator is a multi-purpose machine available in widths of 4.2 and 6.2 m. The aggregates use a simplified unfolding system, where after unlocking the blocking beam, the side sections are unfolded when reversing, then all sections are lowered to the working position using one hydraulic cylinder. The machine is equipped with Φ460 mm toothed discs, behind which there is a kneading roller, it is designed for high-speed first post-harvest cultivation and seed bed preparation. The machine can be equipped with various versions of front tools and packers, thanks to which it will meet all the requirements for equipment used in various modern farming systems - from very shallow tillage to deep soil loosening and mixing of crop residues with it. The versatility of the equipment ensures a reduction in the number of necessary passes, which reduces operating costs and creates the best conditions for the development of the plant.

SPECIFICATION	hydraulically foldable, trailed										
Ring type	Cambrid	Cambridge Φ500		Cambridge Φ530		Cambridge Φ600		Steel-pack Ф600		Zig-zag Φ530	
€ Working width  m	4,2	6,2	4,2	6,2	4,2	6,2	4,2	6,2	4,2	6,2	
Catalog number  id	4120	4121	4122	4123	4124	4125	4126	4127	4128	4129	
Required power  HP	140	210	140	210	160	230	170	240	180	250	
<b>∰</b> Weight  kg	4040	5820	4370	6300	4560	6570	3540	5100	4590	6620	
Number of rings  pcs.	79	119	85	125	79	119	34	50	82	122	

## **OPTIONS**



+ front cutter 7 pieces of Hardox knives in front of the disc section



+ hydraulically adjustable front cross-board

LED lighting

