

FIELD CULTIVATOR



Standard

- 3-point hitch
- spiral rippers behind tractor wheels 2x2 pcs.
- front 9-string roller $\Phi 315$ mm
- four rows of tines 32x12 mm with a double-sided straight share
- double string roller, rear $\Phi 315$ mm
- adjustment and spring pressure, rear string roller trolleys
- smooth adjustment of working depth
- hydraulic folding frame with 2 cylinders
- varnish coating with improved parameters

hydraulically foldable,
mounted

3,6 - 5,6 m



reinforcement
32x12 tines with 32x10
goose foot







front
bar drag





Options

About the machine

The LECH cultivator is designed for pre-sowing soil cultivation. It is used for loosening the top layer of soil, breaking up and crushing lumps of crusted field surface and kneading the ground for better groundwater infiltration. The aggregate is especially useful when growing plants that require a leveled field.

SPECIFICATION	hydraulically foldable, mounted			
 Working width [m]	3,6	4,2	4,9	5,6
ID Catalog number [id]	1007	1010	1013	1016
 Required power [HP]	88-100	102-120	130-140	150-160
 Weight [kg]	1150	1300	1540	1630
 Number of tines [pcs.]	36	42	49	56

OPTIONS	
	extra fot 32x12 tines with 32x10 reinforcement, finished with a goose foot
	bar drag instead of front string rollers
	LED lighting

